

Anchortite Component B

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations.

Revision Date: 03/01/2019 Date of Issue: 02/28/2018 Supersedes SDS Date: 02/28/2018 Version 3.0

Revision Impetus : Text and logo format changes.

SECTION 1: IDENTIFICATION

Product Identifier

Product Name: Anchortite Component B

Synonyms: One component of a two component anchoring grout, Anchortite Component B organic peroxide with inorganic filler and Anchortite Component A polyester resin.

Intended Use of the Product

Polyester Anchoring Grout

Name, Address, and Telephone of the Responsible Party

USA:

Minova USA Inc.
150 Summer Court
Georgetown, KY 40324
T502-863-6800

For SDS Requests:

Call 1-855-266-7422 or email sds.na@orica.com

www.minovaglobal.com

Emergency Telephone Number

Emergency number : For chemical emergencies (24 hour) involving transportation, spill, leak, release, fire or accidents **IN THE U.S. or CANADA CALL: CHEMTREC 1-800-424-9300, Minova CCN 14730.**

Canada:

Minova
576 Arvin Avenue
Stoney Creek, ON - Canada L8E 5P1
T 905-643-1166

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Skin Irrit. 2 H315
Eye Irrit. 2A H319
STOT SE 3 H335
Carc. 1A H350
STOT RE 1 H372

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H315 – Causes skin irritation.
H319 – Causes serious eye irritation.
H335 – May cause respiratory irritation.
H350 – May cause cancer (inhalation).
H372 – Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements (GHS-US)

: P202 – Do not handle until all safety precautions have been read and understood.
P260 – Do not breathe dust.
P264 – Wash hands, forearms, and exposed areas thoroughly after handling.
P270 – Do not eat, drink or smoke when using this product.
P271 – Use only outdoors or in a well-ventilated area.
P280 – Wear protective clothing, protective gloves, eye protection.
P302+P352 – If on skin: Wash with plenty of soap and water.
P305+P338+P351 – If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 – If exposed or concerned: Get medical advice/attention.

Anchortite Component B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P310 – Immediately call a Poison Center or doctor/physician.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

Other Hazards Anchotite Component B component contains quartz “sand”. Inhalation of high levels of quartz “sand” not typical during product use above OSHA Threshold Limit Values may cause lung damage in the form of silicosis and cancer. Anchortite Component A component contains styrene. Inhalation of high levels of styrene vapor not typical during product use above OSHA Threshold Limit Values may cause upper respiratory tract irritation, dizziness, headaches, other central nervous system effects and cancer.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product identifier	% (w/w)	Classification (GHS-US)
Quartz	(CAS No) 14808-60-7	60 – 100	Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372
Limestone	(CAS No) 1317-65-3	7 – 13	Eye Irrit. 2B, H320 STOT SE 3, H335
Calcium hydrogen phosphate, dihydrate	(CAS No) 7789-77-7	1 – 5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Titanium dioxide	(CAS No) 13463-67-7	1 – 5	Eye Irrit. 2B, H320 STOT SE 3, H335
Dibenzoyl peroxide	(CAS No) 94-36-0	0.5 - 1.5	Org. Perox. B, H241 Eye Irrit. 2A, H319 Skin Sens. 1, H317

A range of concentration as prescribed by Controlled Products Regulations has been used where necessary, due to varying composition. Full text of H-phrases: see section 16.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Keep at rest and in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin Contact: Remove contaminated clothing. Rinse affected area with water and soap for several minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. Immediately call a doctor/physician.

Ingestion: Rinse mouth. Do not induce vomiting. If spontaneous vomiting occurs, have victim lean forward with head positioned between the legs to avoid breathing in of vomit, rinse mouth and have victim drink plenty of water. Immediately call a POISON CENTER or doctor/physician. Never give anything by mouth to an unconscious person.

Most Important Symptoms and Effects Both Acute and Delayed

General: Anchotite Component B may cause irritation to eyes, respiratory system and skin. Irritation to eyes can be serious and damage eyes. Anchortite Component A contains styrene. Inhalation of high levels of styrene vapor not typical during product use above OSHA Threshold Limit Values may cause upper respiratory tract irritation, dizziness, headaches, and other central nervous system effects.

Inhalation: Causes irritation to the respiratory tract.

Skin Contact: Causes skin irritation.

Eye Contact: Causes serious eye irritation.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Anchortite Component B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Chronic Symptoms: Anchortite Component B contains quartz “sand”. Inhalation of high levels of quartz “sand” not typical during product use above OSHA Threshold Limit Values may cause lung damage in the form of silicosis and cancer. Anchortite Component A contains styrene. Inhalation of high levels of styrene vapor not typical during product use above OSHA Threshold Limit Values may cause upper respiratory tract irritation, dizziness, headaches, and other central nervous system effects.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use dry chemical powder, alcohol resistant foam, or carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Anchortite Component B not flammable. Anchortite Component A flammable liquid and vapor.

Explosion Hazard: Product is not explosive.

Reactivity: Anchortite Component B may react with organic/inorganic acids, amines and reducing agents. Anchortite Component A (strong) oxidizers.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Firefighters should wear full protective gear.

Hazardous Combustion Products: Anchortite Component B contains oxides of calcium and other metal oxides. Anchortite Component A contains oxides of carbon and nitrogen. As in all fires toxic and noxious fumes.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes or on skin. Do not breathe vapors. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate danger area.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: In the event of a spill or leak of material eliminate ignition sources and ventilate area. Dike and absorb material with inert material and scoop up material. As with all spills, minimize material entering water systems.

Environmental Precautions

Avoid release to the environment.

Methods and Material for Containment and Cleaning Up

For Containment: Place in suitable container. Anchortite Component A and Anchortite Component B should be placed in separate containers.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely.

Reference to Other Sections

See Section 8, Exposure Controls and Personal Protection. See Section 13, Disposal Considerations.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Good housekeeping is needed during storage, transfer, handling, and use of this material to avoid excessive dust accumulation. Never add material to this product unless instructed by Minova.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Always wash your hands immediately after handling this product, and once again before leaving the workplace.

Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Store in a dry, cool place. Store away from direct sunlight or other heat sources which can reduce products usability and shelf-life.

Anchortite Component B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Incompatible Materials: Anchortite Component B organic/inorganic acids, amines and reducing agents. Anchorite Component A (strong) oxidizers.

Specific End Use(s)

Polyester Anchoring Grout

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Quartz (14808-60-7)		
Mexico	OEL TWA (mg/m ³)	0.1 mg/m ³
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³
USA IDLH	US IDLH (mg/m ³)	50 mg/m ³
Alberta	OEL TWA (mg/m ³)	0.025 mg/m ³
British Columbia	OEL TWA (mg/m ³)	0.025 mg/m ³
Manitoba	OEL TWA (mg/m ³)	0.025 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	0.1 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	0.025 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	0.025 mg/m ³
Nunavut	OEL TWA (mg/m ³)	0.3 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	0.3 mg/m ³ (total mass)
Ontario	OEL TWA (mg/m ³)	0.10 mg/m ³ (designated substances regulation)
Prince Edward Island	OEL TWA (mg/m ³)	0.025 mg/m ³
Québec	VEMP (mg/m ³)	0.1 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	0.05 mg/m ³
Yukon	OEL TWA (mg/m ³)	300 particle/mL
Titanium dioxide (13463-67-7)		
Mexico	OEL TWA (mg/m ³)	10 mg/m ³
Mexico	OEL STEL (mg/m ³)	20 mg/m ³
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³
USA IDLH	US IDLH (mg/m ³)	5000 mg/m ³
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	OEL TWA (mg/m ³)	3 mg/m ³
Manitoba	OEL TWA (mg/m ³)	10 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	10 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	10 mg/m ³
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³ (total mass)
Ontario	OEL TWA (mg/m ³)	10 mg/m ³
Prince Edward Island	OEL TWA (mg/m ³)	10 mg/m ³
Québec	VEMP (mg/m ³)	10 mg/m ³ (containing no Asbestos and <1% Crystalline silica)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³
Yukon	OEL STEL (mg/m ³)	20 mg/m ³
Yukon	OEL TWA (mg/m ³)	10 mg/m ³
Dibenzoyl peroxide (94-36-0)		
Mexico	OEL TWA (mg/m ³)	5 mg/m ³
USA ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³

Anchortite Component B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

USA IDLH	US IDLH (mg/m ³)	1500 mg/m ³
Alberta	OEL TWA (mg/m ³)	5 mg/m ³
British Columbia	OEL TWA (mg/m ³)	5 mg/m ³
Manitoba	OEL TWA (mg/m ³)	5 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	5 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	5 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	5 mg/m ³
Nunavut	OEL STEL (mg/m ³)	10 mg/m ³
Nunavut	OEL TWA (mg/m ³)	5 mg/m ³
Northwest Territories	OEL STEL (mg/m ³)	10 mg/m ³
Northwest Territories	OEL TWA (mg/m ³)	5 mg/m ³
Ontario	OEL TWA (mg/m ³)	5 mg/m ³
Prince Edward Island	OEL TWA (mg/m ³)	5 mg/m ³
Québec	VEMP (mg/m ³)	5 mg/m ³
Saskatchewan	OEL STEL (mg/m ³)	10 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	5 mg/m ³
Yukon	OEL STEL (mg/m ³)	5 mg/m ³
Yukon	OEL TWA (mg/m ³)	5 mg/m ³

Limestone (1317-65-3)

Mexico	OEL TWA (mg/m ³)	10 mg/m ³
Mexico	OEL STEL (mg/m ³)	20 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	OEL STEL (mg/m ³)	20 mg/m ³
British Columbia	OEL TWA (mg/m ³)	3 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³ (total mass)
Québec	VEMP (mg/m ³)	10 mg/m ³ (Limestone, containing no Asbestos and <1% Crystalline silica)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³
Yukon	OEL STEL (mg/m ³)	20 mg/m ³
Yukon	OEL TWA (mg/m ³)	10 mg/m ³

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Safety glasses. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Safety glasses or chemical goggles as appropriate to prevent eye contact.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use a NIOSH-approved respirator whenever exposure may exceed established Occupational Exposure Limits.

Anchortite Component B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Grey Powder
Odor	: Sweet
Odor Threshold	: Not applicable
pH	: Not applicable
Relative Evaporation Rate (butyl acetate=1)	: Not applicable
Melting Point	: Not applicable
Freezing Point	: Not applicable
Boiling Point	: Not applicable
Flash Point	: Not applicable
Auto-ignition Temperature	: Not applicable
Decomposition Temperature	: Do not store above 100 °F (38 °C)
Flammability (solid, gas)	: Not applicable
Lower Flammable Limit	: Not applicable
Upper Flammable Limit	: Not applicable
Vapor Pressure	: Not applicable
Relative Vapor Density at 20 °C	: Not applicable
Relative Density	: Not applicable
Specific Gravity	: Not applicable
Solubility	: Negligible
Log Pow	: Not applicable
Log Kow	: Not applicable
Viscosity, Kinematic	: Not applicable
Viscosity, Dynamic	: Not applicable
Explosion Data – Sensitivity to Mechanical Impact	: Not applicable
Explosion Data – Sensitivity to Static Discharge	: Not applicable

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Anchortite Component B may react with organic/inorganic acids, amines and reducing agents. Anchorite Component A (strong) oxidizers.

Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

Possibility of Hazardous Reactions: Hazardous reactions will not occur under normal conditions.

Conditions to Avoid: Do not store above 100 °F (38 °C) and in direct sunlight as this will reduce product's usability and shelf-life.

Incompatible Materials: Anchortite Component B organic/inorganic acids, amines and reducing agents. Anchorite Component A (strong) oxidizers.

Hazardous Decomposition Products: Anchortite Component B other calcium and other metal oxides compounds. Anchorite Component A other carbon and nitrogen compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Anchortite Component B not toxic based on mixture ingredients.

Anchortite Component A Oral: Harmful if swallowed. Dermal: Harmful in contact with skin. Inhalation: Harmful if inhaled.

LD50 and LC50 Data:

Anchortite Component B	
ATE (oral)	500.00 mg/kg body weight
ATE (dust, mist)	1.50 mg/l/4h

Skin Corrosion/Irritation: May cause skin irritation.

Serious Eye Damage/Irritation: May cause serious eye irritation.

Respiratory or Skin Sensitization: No

Anchortite Component B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available

Carcinogenicity: Anchortite Component B component contains quartz "sand". Inhalation of high levels of quartz "sand" not typical during product use above OSHA Threshold Limit Values may cause lung damage in the form of silicosis and cancer. Anchortite Component A component exposure to high levels of styrene through prolonged or repeated exposure not typical during product use may cause cancer and damage to organs. Styrene has been classified by ACGIH, American Conference of Governmental Industrial Hygienists) as a Group 4A – Not classifiable as a human carcinogen. Styrene has been classified by IARC (International Agency for Research on Cancer) as a Group 2B – Possibly Carcinogenic to Humans. Styrene has been classified by NTP (National Toxicology Program) as reasonably anticipated to be a human carcinogen.

Specific Target Organ Toxicity (Repeated Exposure): May cause damage to organs through prolonged or repeated exposure.

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation.

Aspiration Hazard: Do not spray.

Symptoms/Injuries After Inhalation: Irritating to the respiratory system and mucous membranes.

Symptoms/Injuries After Skin Contact: May cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause severe eye irritation.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Refer to Carcinogenicity and Specific Target Organ Toxicity. Effects are dependent on exposure to high levels of quartz "sand" for Anchortite Component B and on exposure to high levels of styrene for Anchortite Component A through prolonged or repeated exposure not typical during product use.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data

Quartz (14808-60-7)	
LD50 Oral Rat	> 5000 mg/kg
Titanium dioxide (13463-67-7)	
LD50 Oral Rat	> 10000 mg/kg
Quartz (14808-60-7)	
IARC Group	1
National Toxicity Program (NTP) Status	Known Human Carcinogens.
Titanium dioxide (13463-67-7)	
IARC Group	2B
Dibenzoyl peroxide (94-36-0)	
IARC Group	3

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Not available

Persistence and Degradability Not available

Bioaccumulative Potential Not available

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: If Anchortite Component B component as supplied becomes a waste, it does not meet the criteria of a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. If Anchortite Component A component as supplied becomes a waste, it meets the criteria of a hazardous waste exhibiting characteristic ignitability as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator.

SECTION 14: TRANSPORT INFORMATION

Anchortite Component B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

In accordance with DOT vehicle shipment “only” this product is exempted from shipment as a regulated DOT hazardous material based on the following criteria. This exemption does not apply to airplane or vessel shipment.

Anchortite Component A has vinyl toluene added which raises the flash point of the material above 100 °F (38 °C) that in accordance with the DOT regulations allows the Anchortite Component A to be classified as a combustible liquid per 49 CFR 172.120. The material is shipped in non-bulk packaging that is exempted from the requirements of 49 CFR 173.150 including packaging. The amount of styrene in each package does not meet the reportable quantity to be regulated as a hazardous substance or marine pollutant.

Anchortite Component B is exempted based on the fact the the benzoyl peroxide falls below the available oxygen regulated level of 0.5 percent per 49 CFR 172.128.

§173.120 Class 3 – Definitions.

(2) A flammable liquid with a flash point at or above 100 °F (38 °C) that does not meet the definition of any other hazard class may be reclassified as a combustible liquid. This provision does not apply to transportation by vessel or aircraft, except where other means of transportation is impracticable.

§173.150 Exceptions for Class 3 (flammable and combustible liquids)

(f) Combustible liquids. (1) A flammable liquid with a flash point at or above 100 °F (38 °C) that does not meet the definition of any other hazard class may be reclassified as a combustible liquid. This provision does not apply to transportation by vessel or aircraft, except where other means of transportation is impracticable.

(2) The requirements of this subchapter do not apply to a material classed as a combustible liquid in a non-bulk packaging unless the combustible liquid is a hazardous substance, a hazardous waste, or a marine pollutant.

§173.128 Class 5, Division 5.2 – Definitions and types.

(a) Definitions. For the purpose of the subchapter, organic peroxide (Division 5.2) means any organic compound containing oxygen (O) in the bivalent –O-O- structure and which may be considered a derivative of hydrogen peroxide, where one or more of the hydrogen atoms have been replaced by organic radicals, unless any of the following paragraphs applies:

(4) The material meets one of the following conditions:

(i) For materials containing more than 1.0 percent but not more than 7.0 percent hydrogen peroxide, the available oxygen content, content (O_a) is not more than 0.5 percent.

14.1 In Accordance With ICAO/IATA/DOT/IMDG: Anchortite Component A is not regulated by DOT vehicle shipment in non-bulk packaging only! Anchortite Component A is regulated if transported by airplane and vessel shipment by ICAO/IATA/IMDG. Anchortite Component B is not regulated for transport.

: III - Minor Danger

National Motor Freight Classification

Anchortite Component A

NMFC Name: Resin Compound **NMFC Number:** 46030 **Class:** 55

Anchortite Component B

NMFC Name: Chemicals, NOI **NMFC Number:** 43940 Sub 2 **Class:** 85

Anchortite Kit (Component A + Component B)

NMFC Name: Resin Compound **NMFC Number:** 46030 **Class:** 55

Tariff Classification Number

3907.91.5000

Anchortite Component A

2505.10.5000

Anchortite Component B

3907.91.5000

Anchortite Kit (Component A + Component B)

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Anchortite Component B

SARA Section 311/312 Hazard Classes

Immediate (acute) health hazard
Delayed (chronic) health hazard

Anchortite Component B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Quartz (14808-60-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Titanium dioxide (13463-67-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Dibenzoyl peroxide (94-36-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on SARA Section 313 (Specific toxic chemical listings)	
SARA Section 313 - Emission Reporting	1.0 %
Limestone (1317-65-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
US State Regulations	
Quartz (14808-60-7)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Titanium dioxide (13463-67-7)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Quartz (14808-60-7)	
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations	
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)	
U.S. - Idaho - Occupational Exposure Limits - Mineral Dusts	
U.S. - Illinois - Toxic Air Contaminant Carcinogens	
U.S. - Illinois - Toxic Air Contaminants	
U.S. - Maine - Chemicals of High Concern	
U.S. - Massachusetts - Right To Know List	
U.S. - Michigan - Occupational Exposure Limits - TWAs	
U.S. - Minnesota - Chemicals of High Concern	
U.S. - Minnesota - Hazardous Substance List	
U.S. - Minnesota - Permissible Exposure Limits - TWAs	
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour	
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - New Jersey - Special Health Hazards Substances List	
U.S. - Oregon - Permissible Exposure Limits - Mineral Dusts	
U.S. - Pennsylvania - RTK (Right to Know) List	
U.S. - Tennessee - Occupational Exposure Limits - TWAs	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	
U.S. - Vermont - Permissible Exposure Limits - TWAs	
U.S. - Washington - Permissible Exposure Limits - STELs	
U.S. - Washington - Permissible Exposure Limits - TWAs	
Titanium dioxide (13463-67-7)	
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)	
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)	
U.S. - Idaho - Occupational Exposure Limits - TWAs	
U.S. - Illinois - Toxic Air Contaminant Carcinogens	
U.S. - Massachusetts - Right To Know List	
U.S. - Michigan - Occupational Exposure Limits - TWAs	
U.S. - Minnesota - Chemicals of High Concern	
U.S. - Minnesota - Hazardous Substance List	

Anchortite Component B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs

Dibenzoyl peroxide (94-36-0)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Delaware - Accidental Release Prevention Regulations - Sufficient Quantities
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Michigan - Process Safety Management Highly Hazardous Chemicals
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS)
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet

Anchortite Component B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet
U.S. - Wyoming - Process Safety Management - Highly Hazardous Chemicals

Limestone (1317-65-3)

U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Massachusetts - Right To Know List
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits - STELS
U.S. - Washington - Permissible Exposure Limits - TWAs

Canadian Regulations

Anchortite Component B

WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------



Quartz (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.
Listed on the Canadian Ingredient Disclosure List

WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
----------------------	------------------------------------------------------------------------------------

Titanium dioxide (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
----------------------	------------------------------------------------------------------------------------

Dibenzoyl peroxide (94-36-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.
Listed on the Canadian Ingredient Disclosure List

WHMIS Classification	Class C - Oxidizing Material Class F - Dangerously Reactive Material Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------

Limestone (1317-65-3)

Listed on Non-Domestic Substances List (NDSL)

WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
----------------------	------------------------------------------------------------------------------------

SECTION 16: OTHER INFORMATION

Revision date : 03/01/2019

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and the Hazardous Products Regulations (WHMIS 2015).

Anchortite Component B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

GHS Full Text Phrases:

Carc. 1A	Carcinogenicity Category 1A
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Org. Perox. B	Organic Peroxide Category B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure

Party Responsible for the Preparation of This Document

Minova USA Inc. SHES Department

Phone Number: 1-502-863-6800

All information contained herein and in any supporting documents is provided for informational purposes only and is as accurate and up-to-date as possible at the time of publication. Since Orica and its related entities cannot anticipate or control the conditions under which this information may be used, users must review this information in the specific context of the intended application and must make their own determinations as to the suitability of this information for such users' purposes. To the maximum extent permitted by law, nothing contained herein and in any supporting documents shall be deemed to be an express or implied warranty, and Orica expressly disclaims all warranties and representations, INCLUDING WITHOUT LIMITATION, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Orica will not be responsible for any loss whatsoever resulting from any use or reliance upon this information.

North America GHS US 2012 & WHMIS